



XSA1000TG Series Spectrum Analyzer

- + Frequency Range from 9 kHz up to 3.6 GHz
- + 150dBm Displayed Average Noise Level
- + Phase Noise -85dBc/Hz @1Gz and offset at 10KHz
- + Total Amplitude Accuracy <1.5dB
- + 10Hz Minimum Resolution Bandwidth (RBW)
- + EMI Pre-compliance Test Kit
- + Up to 1.5 GHz Tracking Generator Kit
- + 10.4 inches display

+ Performance Specifications

Model	XSA1015TG	XSA1036TG
Frequency		
Range	9kHz-1.5 GHz	9kHz-3.6 GHz
Resolution	1Hz	
Frequency span		
Range	0 Hz , 100 Hz to maximum frequency of device	
Accuracy	± span / (swept points -1)	
Internal reference		
Reference frequency	10.000000 MHz	
Reference frequency accuracy	± [(days from last calibrate × freq aging rate) + temperature stability + initial accuracy]	
Temperature stability	<2.5ppm (15°C to 35°C)	
Aging rate	<1ppm/year	
Readout		
Marker frequency resolution	span/ (the number of sweep points -1)	
Uncertainty	± (freq indication × freq reference uncertainty +1%× span +10%× resolution bandwidth + Marker Frequency Resolution)	
Frequency counter		
Resolution	1 Hz , 10 Hz , 100 Hz , 1 kHz	
Accuracy	± (marker freq × freq reference uncertainty + counter resolution)	
Bandwidth		
Resolution bandwidth (-3 dB)	10Hz to 500kHz (in 1 to 10 sequence) , 1MHz , 3MHz	
Resolution filter shape factor	<5 : 1 nominal (Digital implement, similar to Gauss Pattern)	
Accuracy	<5% nominal	
Video bandwidth (-3 dB)	10Hz to 3MHz	

Amplitude Specification

Amplitude and electric level

Amplitude measurement range	DANL to +20 dBm , close the preamplifier	
Reference electric level	-80 dBm to +30 dBm , 0.1dBm steps	
Preamplifier	20 dB , nominal , 9 kHz~1.5 GHz	
Input attenuator range	0~39 dB , 3 dB steps	
Max input DC voltage	50 VDC	
Max continuous power	30dBm , average continuous power	
Displayed average noise level (DANL)		
	Input attenuation 0 dB , 1Hz resolution bandwidth	
Preamp off	1 MHz~10 MHz -130dBm (nominated)	
	10 MHz~1GHz -130dBm (nominated)	
	1GHz~1.5 GHz -128 dBm(nominated)	1GHz~3.6 GHz -128 dBm(nominated)
Preamp on	1 MHz~10 MHz -150dBm (nominated)	
	10 MHz~1GHz -150dBm (nominated)	
	1GHz~1.5 GHz -148 dBm(nominated)	1GHz~3.6 GHz -148 dBm(nominated)
Phase noise		
	20 °C ~30 °C , fc=1 GHz	
Phase noise	<-85 dBc/Hz @10 kHz offset	
	<-100 dBc/Hz @100 kHz offset	
	<-110 dBc/Hz @1 MHz offset	
Level display range		
Log scale coordinate	1dB ~255dB	
Linear scale coordinate	0 to reference level	
level unit	dBm, dBuW, dBpW, dBmV, dBuV, W,V	
Points	201~1001	
Number of traces	5	
Detectors	Positive-peak, negative-peak, sample, normal, RMS	
Trace functions	Clear write, Max Hold, Min Hold, View, Blank, Average	
Frequency response		
	20°C ~30°C , 30%~70% relative humidity, 20 dB input attenuation, reference 50 MHz	
Preamp off	±0.8 dB ;	
Preamp on	±0.9 dB ;	
Accuracy		
Input Attenuation Switching Uncertainty	20°C ~30°C , fc=50 MHz , Preamplifier Off , 20dB RF attenuation , input signal 0~39 dB ±0.5 dB	
Absolute Amplitude Uncertainty	20°C ~30°C , fc=50 MHz , RBW=1 kHz , VBW=1 kHz , peak detector, 20 dB RF attenuation , Preamplifier Off ±0.4 dB , input signal= -20dBm Preamplifier On ±0.5 dB, input signal= -40dBm	

Uncertainty	input signal range 0dbm~-50dbm
	±1.5 dB
VSWR	input 10 dB RF attenuation , 1 MHz~1.5GHz
	<1.5 , nominal

Distortion and spurious response

Second harmonic distortion	$f_c \geq 50$ MHz , Preamp off, signal input -30 dBm, 0 dB RF attenuation, 20 °C to 30 °C
	-65dbc
Third-order intermodulation	$f_c \geq 50$ MHz
	+10 dBm
1 dB Gain Compression	$f_c \geq 50$ MHz , 0 dB RF attenuation , Preamp off , 20 °C to 30 °C
	+2 dBm, nominal
Residual response	connect 50 Ω load at input port , 0 dB input attenuation , 20 °C to 30 °C
	<-85dBm , nominated
Input related spurious	-30 dBm signal at input mixer , 20 °C to 30 °C
	<-60 dBc

Sweep time and triggering

Span range	100Hz≤SPAN≤3GHz 10ms to 3000s zero sweep width 1ms to 3000s
Mode	Continue, single
Trigger	Free run, video, external

Tracking generator

Output frequency range	100 kHz~1.5 GHz
Output power level range	-30 dBm~0 dBm ,
Output power level resolution	1DB
Output flatness	+/-3 dB
Maximum safe reverse level	Average total power : 30 dBm , DC : ±50 VDC

Inputs and Outputs

Front panel RF input connector	50 Ω , N-type female
Front panel track generator output	50 Ω , N-type female
10 M reference input	50 Ω , N-type female

Communication port

	USB HOST, USB DEVICE, LAN, earphone port, and VGA
--	---

General technical specification

Display	TFT LCD , 10.4 inches
Weight (without package)	5 kg
Dimension (W x H x D)	421 x 221 x 115 (mm)
Working temperature	0~40 °C
Storage temperature	-20 °C to +60 °C

